

Vertical Flammability – 60 Second Ignition (FAR 25.853 Appendix F (a) (1) (i) – 1995)

Applicable to products:

- Interior ceiling panels, interior wall panels, partitions,
- Galley structure, large cabinet walls,
- Structural flooring, and
- Materials used in the construction of stowage compartments (other than under seat stowage compartments and compartments for stowing small items such as magazines and maps)

Requirements:

- Must be self-extinguishing when tested vertically in accordance with Appendix F.
- The average burn length may not exceed 6 inches and the average flame time after removal of the flame source may not exceed 15 Seconds.
- Drippings from the test specimen may not continue to flame for more than an average of 3 seconds after falling.

AWTA Test Code T17A (FAR-A)

Sample required Length direction: 3 specimens: 2" x 12" (50.8mm x 304.8mm)
 Width direction: 3 specimens: 2" x 12" (50.8mm x 304.8mm)

Company name	
Company address	
Contact person	
Contact person email	
Contact person phone number	
Name of your product	
Description of your product	
End use of your product	

Delivery Address	Further information
AWTA Product Testing Level 1, 191 Racecourse Rd, Flemington VIC 3031, Australia	AWTA Product Testing Phone: (03) 9371 2400 Email: producttesting@awta.com.au

IMPORTANT NOTE: That by submitting samples for testing **YOU AGREE** that the resulting testing shall be performed under our [terms and conditions for testing and consulting services: www.awta-product-testing.com.au/index.php/about/terms-and-conditions](http://www.awta-product-testing.com.au/index.php/about/terms-and-conditions)